



Model#: AP10TS

Asymmetric application
10,000 lb. 2-Post Lift

Apache Lifts 
— a division of Hergott Automotive Equipment Inc.

TRISYMMETRIC

Apache Lifts enable you to lift both symmetrically and asymmetrically within the same service bay or install the lift in an asymmetric only configuration. This feature allows you to have the lift you want installed the way you want. No other lift offers the same amount of reliability and versatility

The AP10TS features Apache's innovative Trisymmetric design, providing technicians the versatility to lift vehicles both symmetrically and asymmetrically within the same service bay or install the lift in an asymmetric only configuration. This enables you to have the lift you want the way you want.

With adjustable height and width options, double telescoping screw pads, durable powder coat finish, plated arm restraints and pins and many other appealing features, the AP10TS will accommodate the rigorous demands of a full service facility – and afford room to grow with its reasonable cost. Available in red and blue.



FEATURES & BENEFITS

- 3-stage front arms provide greater overall arm sweep
- Set up in a symmetric or asymmetric configuration
- Adjustable height and width options accommodate varying service bay sizes
- Double Telescoping Screw Pads adjust to multiple heights minimizing the need for adapters
- Rubber foot pads minimize stress to vehicles with delicate undercoatings
- Padded overhead shut off system prevents vehicle damage
- Single-point mechanical lock release system allows technician to disengage both columns simultaneously
- Wide rubber door guards protects vehicle from door damage
- Premium powder coat finish provides long-lasting durability
- Plated Arm Restraints and Arm Pins inhibit rust and provide long-lasting durability
- Mirrored "S" shaped column provides:
 - maximized strength
 - more surface area for reliable bearing contact
 - provides clear and safe concave conduit for the bearings



AP10TS

| | Symmetric Application | Asymmetric Application |
|------------------------------------|--------------------------|--------------------------|
| Lifting Capacity* | 10,000 lbs. | |
| Rise Height ¹ | 74 1/2" | |
| Overall Height | 11' 4 1/2" / 11' 10 1/2" | |
| Overall Height (Cylinder Extended) | 11' 10 1/2" | |
| Overall Width ³ | 10' 9" / 11' 3" | 10' 11 1/2" / 11' 5 1/2" |
| Drive-Thru Clearance | 92 3/4" / 98 3/4" | 88 1/2" / 94 1/2" |
| Floor to Overhead Switch | 131" 1/8" / 137 1/8" | |
| Short Arm Reach | 22 3/8" - 41 1/2" | |
| Long Arm Reach | 38 1/4" - 59" | |
| Screw Pad Height ² | 4 3/8" - 6 1/2" | |
| Inside of Columns | 106 3/4" / 112 3/4" | 101 1/2" / 107 1/2" |
| Motor | 2HP, Single Phase, 60Hz | |
| Voltage | 208-230v | |
| Speed of Rise | 48 Seconds | |
| Max Load Per Arm | 2,500 lbs. | |
| Ceiling Height Required | 12' | |

*Lift capacity ratings are based on loads equally distributed on all four arms. ¹Rise height is measured with adjustable screw pads in highest position. ² Specifications are listed without rubber pad, for measurements with rubber pad add 1/4" (6mm). ³ Overall Width of Asymmetric lift is 11' 3" / 11' 9" including Power Unit. [†] Frame engaging adapters (10314 or 10318) are REQUIRED when lifting vehicles with frame construction.

Standard Adapters



Part #10315

Stack Adapter Kit includes
 (4) 3" Stack Extensions
 (2) 6" Stack Extensions
 (2) Organizer Racks with hardware



Part #10318

Set of 4 frame engaging truck adapters.
 *REQUIRED when lifting vehicles with frame construction.

Rubber Door Guards Standard



Arm Coverage



Symmetrical Configuration

3-Stage front and 2-Stage rear arms.

Asymmetrical Configuration

3-Stage front and 2-Stage rear arms.



The Automotive Lift Institute (ALI) certifies that the AP10TS described herein comply with the applicable provisions of the American National Standards ANSI/ALI ALCTV 2011 and are Third Party Validated by the ETL Testing Laboratory.

Apache Lifts Innovations

a division of Hergott
 Automotive Equipment Inc.
 37 McAllister Dr.
 Bloomington ON, NOB 1K0

Apache Lifts Innovations reserves the right to make changes to specifications without notice and without making changes retroactive. Unloading, installation and oil not included.

800-461-1692
 p: 519-658-3738
 f: 519-569-7249
 sales@apachelifts.com